

Cover Keys

Locking Cover Key

Primary Application

Unlocks the thermoplastic cover on quick-coupling valves equipped with locking covers.

Features

- Locks and unlocks the optional locking cover on quick-coupling valves.
- Operates the valve marker compression lock.
- Compatible with models 33DLRC, 33DNP, 44LRC, 44NP, and 5LRC.

Model

- 2049 Cover Key



2049

Hose Swivel

SH Series

Primary Application

Attaches water hose to quick-coupling valve key.

Features

- Swivels up to 360°.
- Allows hose to be pulled in any direction.
- Prevents hose damage.

Specifications

- SH-0
3/4" (20/27) female pipe thread x 3/4" (20/27) male hose thread
- SH-1
1" (26/34) female pipe thread x 3/4" (20/27) male hose thread
- SH-2
1" (26/34) female pipe thread x 1" (26/34) male hose thread
- SH-3
1 1/2" (40/49) female pipe thread x 1" (26/34) male hose thread

Models

- SH-0
- SH-1
- SH-2*
- SH-3

*Available with BSP threads.



SH-0

Pressure Hose Gauge Assembly

PHG

Primary Application

Attaches to Schrader valve on PRS-D pressure regulator to visually read outlet pressure.

Features

- Monitors valve outlet pressure.
- Quick connect hose fitting is simple to connect and disconnect to PRS-D Schrader valve.

Specifications

- 0 to 160 psi (0 to 11,04 bar) gauge provides accurate reading of outlet pressure.
- 36" (91,4 cm) long, high-pressure hose permits easy reading of gauge.

Model

- PHG



PHG

Valve Accessories

Non-Potable Valve Handle Assembly

Primary Application

Purple flow control handle identifies valve as part of a non-potable system.

Features

- Easily field installed.
- Sizes for all Rain Bird commercial valves.

Models

- PGA-NP-HAN1 (1" and 1 1/2" PGA Valves)
- PGA-NP-HAN2 (2" PGA Valves)
- PEB-NP-HAN1 (1" PEB/PESB Valves)
- PEB-NP-HAN2 (1 1/2" and 2" PEB/PESB Valves)
- EFB-GB-NP-HAN (all EFB-CP and GB Valves)
- BPE-NP-HAN (3" BPE/BPES Valves)



BPE-NP-HAN



PEB-NP-HAN PGA-NP-HAN EFB-GB-NP-HAN

