

**Provides
constant
outlet pressure**

Pressure Regulator Valves

APPLICATIONS

- All irrigation systems

SPECIFICATIONS

- 3/4" low flow model: 0.25 to 4.4 GPM
- 3/4" high flow model: 4.5 to 17.6 GPM
- 1 1/2" model: 11 to 35 GPM
- Other models available up to 500 GPM
- Maximum operating pressure: 145 psi

FEATURES & BENEFITS

Easy inline assembly

Low flow model - female inlet/outlet. 3/4" high flow model - female inlet and male outlet.

Sealed regulating module

Available on 3/4" high flow and 1 1/2" pressure regulator.

Built-in indicator on 3/4" high flow and larger models

Indicates when proper outlet pressure is achieved.

Pressure Regulator Ordering Information


Description	psi	GPM	Model Number	Item Number
Low Flow Inline 3/4" FPT Inlet x FPT Outlet	15	0.25 to 4.4	PRV075LF15V2K	00135-000480
	20		PRV075LF20V2K	00135-000490
	25		PRV075LF25V2K	00135-000500
	35		PRV075LF35V2K	00135-000510
	42		PRV075LF42V2K	00135-000520
High Flow 3/4" FPT Inlet x MPT Outlet	15	4.5 to 17.6	PRV075HF15V2K	00135-000430
	20		PRV075HF20V2K	00135-000440
	25		PRV075HF25V2K	00135-000450
	35		PRV075HF35V2K	00135-000460
	45		PRV075HF45V2K	00135-000470
1 1/2" MPT x MPT	15	11 to 35	PRV15015V2K	00135-000530
	20		PRV15020V2K	00135-000540
	25		PRV15025V2K	00135-000550
	35		PRV15035V2K	00135-000560
	45		PRV15045V2K	00135-000570
Replacement Pressure Regulating Module	15		PRVU15V2K	00135-000595
	20		PRVU20V2K	00135-000600
	25		PRVU25V2K	00135-000610
	35		PRVU35V2K	00135-000620
	45		PRVU45V2K	00135-000630



3/4" Low Flow



3/4" High Flow



Exploded view of 3/4" High Flow Valve with replaceable Pressure Regulating module.



1 1/2"