



GUARDSHACK™

Lift-Off Models

Never any sharp corners or edges; always powder coated to exacting standards for lasting durability. Pioneering beautiful design safe for children and pedestrians.

It's no surprise that the GS-1 & GS-2 are two of our most popular products. Over four dozen different backflows fit into these units.

Model	Type	Internal Dimension W x H x L	EncPad™ Sold Separately	FrostGuard™ Sold Separately
GS-.5	Lift-Off	10" x 18" x 12"	EP-.5	N/A
GS-1	Lift-Off	10" x 24" x 22"	EP-1	FG-1
GS-2	Lift-Off	10" x 24" x 30"	EP-2	FG-2
GS-3.3	Lift-Off	16" x 30" x 30"	EP-2	FG-3.3

Fabrication & Powder Coat Specifications:

1¼" schedule 40 A.S.T.M. A-53 grade A.E.W. steel framework with 1" x 1" x ¼" angle iron: ½" #13 gauge diamond pattern rolled expanded metal. Expanded metal die formed for uniformity. All welded construction maximum 4" on center.

State-of-the-art aeronautics industry five step metal cleaning process and iron phosphate solution treatment. Units preheated before applying 2.0-4.0 mil thickness polyester powder to A.S.T.M. D-2794 Impact Resistant and A.S.T.M. D-3359 Adhesive Specifications

Warranty: BPDIGuardShack warranties this product for one (1) year from the date of purchase to be free of defects in material and workmanship. All claims must be made known to BPDIGuardShack in writing within 30 days of the defect becoming known to the purchaser. There are no warranties that extend beyond those described herein, either expressed or implied. BPDIGuardShack reserves the sole right, at it's own option to repair or replace any defective product, and shall exclude any damage caused by accident, misuse or abuse of the product. In no case shall BPDIGuardShack be liable for any incidental or consequential damages what-so-ever.

GUARDSHACK™

www.GuardShackEnclosures.com

800-266-5411

