



Xeri-Bug™ Emitters

Point Source Emission Devices

Ideal for watering the root zones of plants, trees, and container plants. Xeri-Bugs emit water at rates of 0.5, 1.0 and 2.0 gallons-per-hour (GPH) which allows soils to absorb water more completely into the root zones of plants. Xeri-Bugs are an ideal choice for those wishing to conserve water or eliminate excessive run-off.

Features & Benefits:

- Flow-rates from 0.5 to 2.0 GPH (1,89 to 7,57 l/h).
- Pressure-compensating design delivers uniform flow throughout a wide pressure range (15 to 50 psi; 1,0 to 3,5 bars).
- Available with self-piercing inlet barb to permit one-step emitter insertion into 1/2" or 3/4" drip tubing when installed with the XM-Tool.
- Inlet and outlet barb securely retains 1/4" distribution tubing (DT-025 or PT-025).
- Available with 10-32 threaded inlet that easily threads into a polyflex riser (see page 245).
- Use Xeri-Bugs (barb or 10-32 models) with the Xeri-Bird™ 8 multioutlet device (see page 240).
- Available with 1/2" (15/21) FPT inlet that easily threads onto a 1/2" PVC riser.
- Self-flushing action minimizes clogging.
- Made from highly inert materials that are resistant to chemicals.
- Durable plastic construction is UV-resistant.
- Color-code inlet identifies flow rate.

Operating Range

- Flow: 0.5 to 2.0 GPH (1,89 to 7,57 l/h)
- Pressure: 15 to 50 psi (1,0 to 3,5 bars)
- Filtration: 150 to 200 mesh (75 to 100 micron)

Models

- XB-05PC (Blue) Barb inlet; 0.5 GPH (1,89 l/h)
- XB-10PC (Black) Barb inlet; 1.0 GPH (3,79 l/h)
- XB-20PC (Red) Barb inlet; 2.0 GPH (7,57 l/h)
- XB-05PC-1032 (Blue) 10-32 Threaded inlet; 0.5 GPH (1,89



[click to enlarge](#)



[click to enlarge](#)



[click to enlarge](#)



l/h)

- XB-10PC-1032 (Black) 10-32 Threaded inlet; 1.0 GPH (3,79 l/h)
- XB-20PC-1032 (Red) 10-32 Threaded inlet; 2.0 GPH (7,57 l/h)
- XBT-10PC 1/2" (15/21) FPT inlet; 1.0 GPH (3,79 l/h)
- XBT-20PC 1/2" (15/21) FPT inlet; 2.0 GPH (7,57 l/h)

Copyright © 1996-2008, Rain Bird Corporation.