Residential/Commercial

RADIUS 8' to 30'

MP ROTATORS SAVE MORE WITH 30% INCREASED EFFICIENCY OVER SPRAYS.

FEATURES

- True matched precipitation any arc or radius setting
- Radius can be reduced up to 25% on all models
- Color-coded for easy identification
- Double-pop feature keeps dirt and debris out of nozzle
- Removable filter screen prevents large objects from clogging nozzle
- Low precipitation rate
- Wind-resistant multi-stream technology
- Adjustable arc and radius offer timely and precise settings

ADVANCED FEATURES

- Ratchet mechanism prevents damage when attempting to reduce radius too far
- Models can only be adjusted while water is running

OPERATING SPECIFICATIONS

Recommended operating pressure: 40 PSI

Models can only be adjusted while water is running

OPTIONS

Pair with Pro-Spray PRS40 to achieve pressure regulation at the head of 40 PSI

Adding "HT" will specify male threaded nozzles



SPECIFICATIONBUILDER

MP1000-210 8' to 15' radius, adjustable from 210° to 270°

MODELS OPTIONS MP1000-90 = 8' to 15' radius, adjustable from 90° to 210° (blank) = No optionMP1000-210 = 8' to 15' radius, adjustable from 210° to 270° HT = Male thread version MP1000-360 = 8' to 15' radius, 360° MP2000-90 = 13' to 21' radius, adjustable from 90° to 210° MP2000-210 = 13' to 21' radius, adjustable from 210° to 270° $MP2000-360 = 13' \text{ to } 21' \text{ radius, } 360^\circ$ MP3000-90 = 22' to 30' radius, adjustable from 90° to 210° MP3000-210 = 22' to 30' radius, adjustable from 210° to 270° MP3000-360 = 22' to 30' radius, 360° MPLCS515 = Left corner strip 5' x 15' (MP Rotators are MPRCS515 = Right corner strip 5' x 15' designed to operate MPSS530 = Side strip 5' x 30' in conjunction with a pop-up sprinkler or MPCORNER = 8' to 15' radius, adjustable from 45° to 105° shrub adapter.) EXAMPLE





 Applies additional water first 3' from the pop-up when head to head coverage is not available