## **PRO-SPRAY®**

APPLICATION

Residential/Commercial

MODELS

Shrub, 2", 3", 4", 6", 12"

## **RESIDENTIAL OR COMMERCIAL,** PROS-00: THIS VERSATILE SPRINKLER IS THE Inlet size: 1/2" Female NPT CONTRACTOR'S CHOICE. **FEATURES** Application: Residential/commercial PROS-02: Overall height: 4" • Models: Shrub, 2", 3", 4", 6", 12" Exposed diameter: 21/4" No side inlet (NSI) version available in 6" and 12" Inlet size: 1/2" Female NPT Warranty period: 5 years ADVANCED FEATURES •• Co-molded wiper seal with UV •• Heavy-duty retraction spring resistant material • Innovative directional flush plug design •• Body cap won't leak under high pressure Reclaimed purple body cap (optional) • Drain check valve (optional) PROS-03: Overall height: 5" • Compatible with all female threaded nozzles Exposed diameter: 2<sup>1</sup>/<sub>4</sub> Inlet size: 1/2" Female NPT **OPERATING SPECIFICATIONS** Recommended pressure range: 15 to 70 PSI FACTORY INSTALLED OPTIONS Drain check valve (up to 10' of elevation) Reclaimed water ID cap USER INSTALLED OPTIONS PROS-04: Overall height: 57/8" Drain check valve (up to 10' of elevation; Exposed diameter: 21/4" P/N 437400) Inlet size: 1/2" Female NPT Reclaimed water ID cap (P/N 458520) Snap-on reclaimed cover (P/N PROSRCCAP) PRO-SPRAY FIXED PRO ADJUSTABLE WORKS BEST WITH MP ROTATOR NOZZLES ARC NOZZLES PROS-06: Overall height: 834" PROS-06-NSI (right): Exposed diameter: 21/4" SPECIFICATIONBUILDER www.hunterindustries.com/PROSPRAY Inlet size: 1/2" Female NPT **STANDARD MODELS OPTIONS** PROS-00 = Shrub adapter (blank) = No option CV = Factory-installed drain check valve PROS-02 = 2" pop-up (pop-up models only) CV-R = Factory-installed reclaimed body cap PROS-03 = 3" pop-up (shrub molded in purple) PROS-04 = 4" pop-up 6" and 12" models ordered as CV will come as PROS-06 = 6" pop-up no side inlet PROS-06-NSI = 6" pop-up with no side inlet PROS-12 = 12" pop-up PROS-12-NSI = 12" pop-up with no side inlet EXAMPLES PROS-12: Overall height: 161/8" PROS-04 - 10A 4" pop-up, and 10' adjustable nozzle PROS-12-NSI (right) PROS-06 - CV - 12H 6" pop-up, drain check valve, and 12' half circle nozzle Exposed diameter: 21/4" **PROS-12 - CV-R - RCS** | 12" pop-up, drain check valve, reclaimed body cap, and right corner strip Inlet size: ½" Female NPT

