

PRO ADJUSTABLE NOZZLES

PRO ADJUSTABLE NOZZLES ARE THE ALL-IN-ONE CHOICE FOR OPTIMAL COVERAGE.

FEATURES

- Crisp, well-defined edges
- Matched precipitation rate of 8' to 17'
- Easy grip top for simple adjustment
- Designed with large water droplets to withstand light winds
- Even distribution results in beautiful pattern
- New 4' and 6' Pro Adjustable Nozzles provide additional flexibility
- Color-coded for easy field identification
- Adjustable from 0° to 360°

OPERATING SPECIFICATIONS

Recommended operating pressure: 30 PSI

Specify the new Pro-Spray® PRS30 pop-up for accurate pressure regulation of 30 PSI

Pro Adjustable Nozzles Performance Data										
Arc	Pressure PSI	4 Foot Radius Adjustable: 0° - 360° Trajectory: 0° Color Code: Lt. Green				6 Foot Radius Adjustable: 0° - 360° Trajectory: 0° Color Code: Lt. Blue				
		Radius ft.	Flow GPM	Precip in/hr		Radius ft.	Flow GPM	Precip in/hr		
45°	20	3	0.11	5.44	6.28	5	0.15	3.21	3.70	
	25	3	0.13	6.02	6.95	5	0.15	3.21	3.70	
	30	4	0.13	6.45	7.45	6	0.18	3.85	4.45	
	35	4	0.14	6.74	7.78	6	0.18	3.85	4.45	
	40	4	0.16	7.70	8.89	6	0.19	4.06	4.69	
90°	20	3	0.19	4.57	5.28	5	0.30	3.21	3.70	
	25	3	0.20	4.81	5.56	5	0.31	3.32	3.83	
	30	4	0.28	6.74	7.78	6	0.37	3.96	4.57	
	35	4	0.24	5.78	6.67	6	0.38	4.06	4.69	
120°	20	3	0.28	5.05	5.84	5	0.37	2.97	3.43	
	25	3	0.30	5.32	6.15	5	0.38	3.05	3.52	
	30	4	0.34	6.14	7.09	6	0.44	3.53	4.08	
	35	4	0.34	6.14	7.09	6	0.46	3.69	4.26	
180°	20	3	0.34	4.09	4.72	5	0.50	2.67	3.09	
	25	3	0.38	4.57	5.28	5	0.54	2.89	3.33	
	30	4	0.45	5.41	6.25	6	0.60	3.21	3.70	
	35	4	0.46	5.53	6.39	6	0.64	3.42	3.95	
240°	20	3	0.58	5.23	6.04	5	0.73	2.93	0.85	
	25	3	0.62	5.59	6.46	5	0.78	3.13	0.90	
	30	4	0.68	6.13	7.08	6	0.88	3.53	1.02	
	35	4	0.74	6.68	7.71	6	0.92	3.69	1.07	
270°	20	4	0.80	7.22	8.34	6	1.02	4.09	1.18	
	20	3	0.59	4.73	5.46	5	0.88	3.14	3.62	
	25	3	0.66	5.29	6.11	5	0.98	3.49	4.03	
	30	4	0.73	5.86	6.76	6	1.10	3.92	4.53	
360°	35	4	0.76	6.10	7.04	6	1.15	4.10	4.73	
	40	4	0.80	6.42	7.41	6	1.20	4.28	4.94	
	20	3	0.66	3.97	4.58	5	1.05	2.81	3.24	
	25	3	0.72	4.33	5.00	5	1.10	2.94	3.40	
30	4	0.80	4.81	5.56	6	1.26	3.37	3.89		
35	4	0.86	5.17	5.97	6	1.30	3.48	4.01		
40	4	0.90	5.41	6.25	6	1.40	3.74	4.32		

Note: The Pro-Spray PRS30's built-in pressure regulator controls output to a maximum of 30 PSI. Optimum nozzle performance shown in bold.

